



P110i

VALUE SERIES



ZEBRA P110i
SINGLE SIDED CARD PRINTER

Affordable Plastic Card Personalisation

Reliable, compact and easy to use, the P110i is Zebra's most affordable color card printer. The sleek design uses high strength plastics and advanced electronics for reduced size and weight and outstanding performance, all at a great price. The P110i delivers consistent, high quality printing and trusted Zebra dependability.

The Zebra P110i is a reliable, compact and easy to use card printer that delivers outstanding performance at a great price. The P110i gives you versatility and cost effectiveness for a wide variety of applications:

- » Employee ID and Access cards
- » Student and Faculty ID's
- » Membership cards
- » Personalized Loyalty and Gift cards

Zebra P110i Advantages

Versatile: Print in full color or monochrome. Choose automatic multi-card feed or CardSense™ single card feed. Compact, sleek design lets you put the P110i just about anywhere.

Easy-to-Use: Intuitive design reduces training costs. Blue touch points indicate user touchable features. Translucent card cover allows you to see when card supply is running low. No-tools-necessary printhead replacement.

Innovative Patent-Pending Technology: P110i uses high strength plastics and advanced electronics for reduced size and weight and outstanding performance. Easy to replace Load-N-Go™ ribbon cartridge with integrated card cleaning roller features automatic set-up and low ribbon warning indicator.

The Zebra P110i. Small printer, big statement.

P110i

Card Printer Product Specifications



General Specifications

- » Integrated feeder
- » Load-N-Go™ drop-in ribbon cartridge
- » 16-digit LCD display
- » Windows® drivers for 2000 and XP
- » 2 year printer warranty
- » 2 year (unlimited passes) printhead warranty

Printing

- » Color dye sublimation or monochrome thermal transfer
- » 30 seconds per card full-color single-sided (YMCKO)
- » 300 dpi (11.8 dots/mm) print resolution

Bar Codes

- » Code 39, Code 128 B & C with & without check digit
- » 2 of 5 & 2 of 5 Interleaved
- » UPC-A, EAN 8 & EAN 13
- » PDF-417 2D bar code
- » other symbologies can be printed via Windows drivers

Card Specifications

- » Types: PVC, PVC Composite.
- » Card width/length: ISO CR-80-ISO 7810, 54mm x 86mm
- » Magnetic Stripe-ISO 7811
- » Smart Card-ISO 7816-2
- » Card thickness: 30 mil (.76mm)
- » Card feeder capacity: 100 cards (30 mil)
- » Card output hopper capacity: 45 cards (30 mil)

Communications Interface

- » USB 1.1 (cable included)

Ribbon Specifications*

- » Load-N-Go™ ribbon cartridge with integrated cardclean
- » i Series technology
- » YMCKO: 200 cards/cartridge
- » Monochrome: 1000 cards/cartridge
- » Monochrome Ribbons: black, blue, or white

Mechanical

- » Width: 201mm
- » Depth: 328 mm
- » Height: 216 mm
- » Weight: 4.3 kg

Electrical

- » 110 ~ 240 Volts AC, 50 ~ 60 Hz (auto switching)
- » 16MB image memory standard
- » FCC Class B, CE, UL and CUL approved

Environmental

- » Operating Temperature: 60°F to 86°F (15°C to 30°C)
- » Operating Humidity: 20% to 65% non-condensing
- » Storage Temperature: 23°F to 158°F (-5°C to 70°C)
- » Storage Humidity: 20% to 70% non-condensing
- » Ventilation: Free air

Options

- » Magnetic encoder (30 mil cards only), 3 track HiCo/LoCo
- » CardSense™ single-feed kit



**Card
Printer
Solutions**